



土被り早見表 (3)

適用条件

1. 溝型
2. コンクリート基礎
3. 土の単位重量 $\gamma = 18\text{kN/m}^3$
4. 活荷重：T荷重

単位：m

呼び径	1種		2種		1種	2種
	90°		90°		180°	180°
	下限	上限	下限	上限	上限	上限
200		6.8		9.8	9.6	13.6
250		5.4		7.9	7.8	11.1
300		4.8		7.2	6.9	10.1
350		4.5		6.7	6.6	9.4
400	0.6	4.4		7.0	6.4	9.8
450	0.6	4.2		7.0	6.3	9.8
500	0.6	4.1		7.2	6.1	10.0
600	0.6	4.0		7.1	5.9	10.0
700	0.7	3.7		6.8	5.6	9.5
800	0.7	3.6		6.5	5.4	9.1
900	0.7	3.4		6.3	5.3	8.9
1000	0.8	3.3		6.1	5.2	8.7
1100	0.8	3.1		5.9	5.0	8.4
1200	0.9	3.0		5.7	4.8	8.1
1350	0.9	2.7		5.3	4.5	7.6
1500	1.0	2.6		5.1	4.4	7.3
1650	1.0	2.5		4.9	4.3	7.1
1800	1.1	2.4		4.8	4.2	7.0
2000	1.1	2.3		4.6	4.1	6.8
2200	1.2	2.2	0.6	4.5	4.0	6.6
2400	1.2	2.2	0.6	4.4	4.0	6.5
2600	1.2	2.2	0.6	4.3	4.0	6.4
2800	1.2	2.2	0.6	4.3	4.0	6.3
3000	1.2	2.2	0.6	4.3	4.0	6.3

※ 空欄については、別途お問い合わせ下さい。
(道路土工による下限値は0.5)