



FSR					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
4.00-9	2	W/T	114	458	3.00D
4.50-10	4	W/T	120	488	3.00D
4.00-12	4	W/T	113	538	3.00D
4.00-15	4	W/T	113	613	3.00D
5.00-15	4	W/T	133	660	3.00D
6.00-16	4	W/T	167	737	4.00E
6.50-16	6	W/T	180	763	4.50E
7.50-16	6	W/T	210	815	5.50F
6.00-19	6	W/T	164	818	4.00E



FSM					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
7.50-16	6	W/T	211	808	5.50F



ALOO					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
4.00-16	2	W/T	108	650	3.00D
4.40-21	2	W/T	118	800	2.75D
4.40-21	4	W/T	120	800	2.75D
130/90-21AG	-	W/T	120	800	2.75D



AROO					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
3.50-5	2	W/T-T/L	93	308	3.00SP
4.00-7	2	W/T	111	400	3.00D
4.00-8	2	W/T	111	445	3.00D
4.00-10	2	W/T	111	492	3.00D
4.50-10	2	W/T	118	515	3.00D
4.00-12	2	W/T	110	540	3.00D
5-12	2	W/T	125	550	4-JA
5.00-12	2	W/T	133	581	3.00D
6-12	2	W/T	158	600	5-JA
6.00-12	2	W/T	157	636	4.00E
6.00-12	4	W/T	160	636	4.00E
5-14	4	W/T	128	605	4-JA
6-14	4	W/T	155	653	5-JA

■ CULTIVATOR



U10L					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
5-12	2	W/T-T/L	126	545	4-JA
5.00-12	2	W/T-T/L	131	573	3.00D
6-12	2	T/L	158	600	5-JA
6.00-12	2	W/T-T/L	154	629	4-JA



TA10					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
4.00-12	2	T/L	111	525	3.00D



No Image

※商品外観が異なりますので、詳しくはご相談ください。

A10L					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
3.00-12	4	W/T	70	457	1.85



TA					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
3.50-5	2	W/T	100	300	3.00SP
3.50-6	2	W/T-T/L	93	320	3.00SP
100/85D6	2	T/L	100	330	3.00
3.50-7	2	W/T-T/L	98	347	3.00D
4.00-7	2	W/T-T/L	110	397	3.00D
4.00-8	2	W/T-T/L	111	435	3.00D
4.00-9	2	W/T-T/L	111	458	3.00D
4.50-10	2	W/T-T/L	111	483	3.00D
4.50-10	2	W/T	123	510	3.00D
4.00-12	2	W/T-T/L	111	540	3.00D
5-12	2	W/T	125	550	4-JA
5.00-12	2	W/T-T/L	133	581	3.00D
6-12	2	W/T-T/L	158	600	5-JA
6.00-12	2	W/T-T/L	157	636	4.00E
6-14	2	W/T	162	657	5-JA

■ IMPLEMENT



FI 2					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
11.5/80-15	10	T/L	332	842	10-JJ

No Image

※商品外観が異なりますので、詳しくはご相談ください。

FI 3					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
9.00-15	8	W/T	252	850	6-LB



AL					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
9.00-13	6	W/T	254	792	5-1/2K

■ RICE PLANTING MACHINE



ATOO					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
300-16	4	W/T	76	620	1.85
2.50-17	4	W/T	60	604	1.60A
2.75-17	4	W/T	70	600	1.85
3.00-17	4	W/T	76	650	1.85
2.50-18	4	W/T	60	625	1.60A
3.00-23	4	W/T	80	765	MT1.85
3.00-25	4	W/T	76	815	SP1.85
3.00-26	4	W/T	80	865	MT1.85
3.00-28	4	W/T	80	900	MT1.85