

## KENDA

### UTILITY



#### K284 FRONT MAX

タイヤサイズ	PR	TYPE	総幅(mm)	外径(mm)	リム(inch)	荷重(kgs)
20X7.00-8	2	TL	183	523	8X5.5AT	89
22X11.00-8	2	TL	264	564	8X9.0AT	155
21X8.00-9	2	TL	185	526	9X6.5AT	103
21X8.00-9	4	TL	185	526	9X6.5AT	103
21X7.00-10	2	TL	180	526	10X5.5AT	93
21X7.00-10	4	TL	180	526	10X5.5AT	93
22X8.00-10	2	TL	180	534	10X5.5AT	109
22X8.00-10	4	TL	180	534	10X5.5AT	109
22X8.00-10	6	TL	180	530	10X5.5AT	125
22X11.00-10	2	TL	262	573	10X9.0AT	150
23X8.00-11	2	TL	195	594	11X6.5AT	115
23X8.00-11	4	TL	195	594	11X6.5AT	115
23X8.00-11	6	TL	195	590	11X6.5AT	132
23.5X8.00-11	2	TL	195	594	11X6.5AT	115



#### K290 SCORPION

タイヤサイズ	PR	TYPE	総幅(mm)	外径(mm)	リム(inch)	荷重(kgs)
145/70-6	2	TL	135	360	6X4.5AT	75
145/70-6	4	TL	135	360	6X4.5AT	75
16X8.00-7	2	TL	190	390	7X6.5AT	100
18X9.50-8	2	TL	224	468	8X7.0AT	106
18X9.50-8	4	TL	224	468	8X7.0AT	106
19X7.00-8	2	TL	176	482	8X5.50AT	106
19X7.00-8	4	TL	174	482	8X5.50AT	106
20X7.00-8	2	TL	174	482	8X5.50AT	87.5
20X7.00-8	4	TL	174	482	8X5.50AT	87.5
20X10.00-8	2	TL	235	513	8X8.0AT	121
22X10.00-8	2	TL	242	547	8X8.0AT	121
22X11.00-8	2	TL	255	550	8X9.0AT	155
22X11.00-8	4	TL	255	550	8X9.0AT	155
20X10.00-9	2	TL	231	516	9X8.0AT	118
20X10.00-9	4	TL	231	516	9X8.0AT	118
25X12.00-9	2	TL	279	610	9X9.5AT	195
24X9.00-11	2	TL	239	647	11X7.0AT	140



#### K570

タイヤサイズ	PR	TYPE	総幅(mm)	外径(mm)	リム(inch)	荷重(kgs)
145/70-6	4	TL	141	360	6X4.5AT	165
AT16X7-7[165/65-7]	4	TL	182	403	7X6.5AT	100
AT16X8-7[165/65-7]	4	TL	182	404	7X6.5AT	100



#### K299 BEAR CLAW

タイヤサイズ	PR	TYPE	総幅(mm)	外径(mm)	リム(inch)	荷重(kgs)
22X12.00-8	6	TL	288	540	8X9.5AT	195
22X12.00-9	6	TL	273	562	9X9.5AT	195
AT22X12-9	6	TL	271	549	9X9.0AT	224
25X12.50-9	6	TL	290	625	9X9.5AT	224
25X12.50-9	6	TL	290	625	9X9.5AT	224
22X8.00-10	6	TL	215	546	10X6.0AT	125
22X12.00-10	6	TL	283	535	10X9.5AT	195
23X7.00-10	6	TL	179	567	10X5.5AT	125
23X7.00-10	6	TL	183	578	10X5.5AT	165
AT23X10-10	6	TL	258	584	10X8.0AT	170
23X10.00-10	6	TL	273	610	10X8.0AT	265
24X11.00-10	6	TL	267	590	10X9.0AT	200
25X12.00-10	6	TL	295	615	10X9.5AT	224
25X12.50-10	6	TL	295	615	10X9.5AT	224
25X12.50-10	8	TL	304	640	12X10.0AT	1120
AT22X7-11	6	TL	175	559	11X5.5AT	115
23X8.00-11	6	TL	198	580	11X6.5AT	132
24X8.00-11	6	TL	210	622	11X6.5AT	145
24X9.00-11	6	TL	225	603	11X7.0AT	165
AT24X10-11	6	TL	240	600	11X7.5AT	180

#### K299 BEAR CLAW

25X8.00-11	6	TL	210	622	11X6.5AT	155
25X10.00-11	6	TL	243	621	11X8.0AT	190
25X12.50-11	6	TL	292	620	11X9.5AT	224
24X8.00-12	6	TL	195	592	12X6.5AT	140
24X8.00-12	6	TL	192	595	12X6.0AT	224
AT24X8-12	6	TL	190	592	12X6.0AT	140
24X10.00-12	6	TL	243	610	12X8.0AT	250
25X8.00-12	6	TL	205	618	12X6.5AT	155
AT25X8-12	6	TL	211	618	12X7.0AT	155
25X10.00-12	6	TL	232	623	12X8.0AT	190
25X12.50-12	6	TL	290	640	12X9.5AT	224
AT25X12.50-12	6	TL	290	640	12X9.5AT	224
AT26X9-12	6	TL	228	660	12X7.0AT	190
AT26X11-12	6	TL	279	665	12X9.0AT	218
AT27X9-12	6	TL	230	686	12X7.0AT	200
AT27X11-12	6	TL	279	686	12X9.0AT	224
22X12.00-8	4	TL	285	545	8X9.5AT	170
22X12.00-9	4	TL	280	566	9X9.5AT	170
25X12.50-9	4	TL	285	622	9X9.5AT	195
22X8.00-10	4	TL	215	560	10X6.0AT	109
22X12.00-10	4	TL	289	542	10X10.0AT	170
23X7.00-10	4	TL	176	565	10X5.5AT	109
24X11.00-10	4	TL	267	596	10X9.0AT	175
25X12.50-10	4	TL	298	615	10X9.5AT	195
23X8.00-11	4	TL	197	584	11X6.5AT	115
24X8.00-11	4	TL	210	631	11X6.5AT	125
24X9.00-11	4	TL	226	605	11X7.0AT	140
AT24X10-11	4	TL	242	598	11X7.5AT	155
25X8.00-11	4	TL	213	625	11X6.5AT	125
25X10.00-11	4	TL	243	625	11X8.0AT	155
25X12.50-11	4	TL	292	620	11X9.5AT	195
AT24X8-12	4	TL	195	594	12X6.5AT	121
24X8.00-12	4	TL	195	594	12X6.5AT	121
25X8.00-12	4	TL	205	625	12X6.5AT	132
25X10.00-12	4	TL	236	623	12X8.0AT	165
AT25X12.5-12	4	TL	290	640	12X9.5AT	195
25X12.50-12	4	TL	290	640	12X9.5AT	195
AT26X9-12	4	TL	233	660	12X7.0AT	175

#### K530F PATHFINDER

タイヤサイズ	PR	TYPE	総幅(mm)	外径(mm)	リム(inch)	荷重(kgs)
16X8.00-7	2	TL	188	397	7X6.5AT	100
18X7.00-7	2	TL	175	438	7X6.0AT	87.5
19X7.00-8	2	TL	178	478	8X6.0AT	106
19X7.00-8	4	TL	189	496	8X5.5AT	308
AT21X7-10	4	TL	175	520	10X5.5AT	92.5
AT21X7-10	6	TL	175	526	10X5.5AT	150
AT22X7-10	4	TL	182	552	10X5.5AT	100
23X8.00-11	2	TL	188	585	11X6.5AT	95
23X8.00-11	4	TL	207	586	11X6.5AT	115
AT23X8-12	4	TL	185	586	12X6.0AT	112
AT23X8-12	4	TL	185	586	12X6.0AT	115
AT24X8-12	2	TL	195	590	12X6.5AT	100
AT24X8-12	4	TL	195	600	12X6.5AT	121
AT24X8-12	6	TL	195	597	12X6.5AT	180
AT25X8-12	4	TL	197	635	12X6.5AT	132
25X8.00-12	2	TL	199	624	12X6.5AT	109
25X8.00-12	4	TL	198	624	12X6.5AT	132

