



T10H					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
11.2-24	4	W/T	281	1095	W-10
12.4-24	4	W/T	324	1161	W-11
13.6-24	4	W/T	345	1210	W-12
9.5-26	4	W/T	236	1100	W-8
11.2-26	4	W/T	279	1155	W-10
12.4-26	4	W/T	310	1210	W-11
13.6-26	4	W/T	340	1260	W-12
11.2-28	4	W/T	279	1205	W-10
12.4-28	4	W/T	317	1260	W-11
13.6-28	4	W/T	340	1310	W-12
13.6-28	6	W/T	340	1310	W-12



FSLSC					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
11.2-24 (FSLSD)	4	W/T	280	1095	W-10
12.4-24	4	W/T	314	1150	W-11
13.6-24	4	W/T	345	1210	W-12
12.4-26 (FSL)	4	W/T	322	1244	W-11
12.4-26	4	W/T	315	1210	W-11
13.6-26	4	W/T	345	1260	W-12
12.4-28	4	W/T	314	1262	W-11
13.6-28	6	W/T	345	1310	W-12
14.9-28 (FSL)	6	W/T	380	1406	W-13
16.9-30	6	W/T	429	1512	W-15L
12.4-32	6	W/T	315	1358	W-11
12.4-32	6	W/T	315	1358	W-11
12.4-36	6	W/T	319	1465	W-11
13.6-38	6	W/T	348	1578	W-12



FH80					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
18.4-34	6	W/T	467	1635	W-16L



FSLH					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
8-18	4	W/T	207	840	W-7
12.4-24	6	W/T	317	1150	W-11
16.9-34	6	W/T	440	1587	W-15L
14.9-38	6	W/T	390	1618	W-13



FSLM ※打ち消し線表記は生産中止					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
4.50-10	4	W/T	120	510	3,00D
6-10	4	W/T	155	550	5-JA
5-12	2	W/T	123	550	4-JA
5-12	4	W/T	123	550	4-JA
5.00-12	2	W/T	131	581	3,00D
5.00-12	4	W/T	131	581	3,00D
6-12	4	W/T	155	600	5-JA
6.00-12	4	W/T	162	636	4.00E
6.00-12	6	W/T	163	638	4.00E
5-14	4	W/T	128	605	4-JA
6-14	2	W/T	155	653	5-JA
6-14	4	W/T	158	653	5-JA
7-14	4	W/T	174	690	5-JA
7-16	4	W/T	170	740	5-JA
8-16	4	W/T	197	789	5-JA
4.00-18	4	W/T	108	690	2.75D
8-18	4	W/T	207	840	W-7
8-18	6	W/T	207	840	W-7
7.2-20	4	W/T	179	845	W-6
8.3-20	4	W/T	209	890	W-7
8.3-20	6	W/T	209	890	W-7



FSLM ※打ち消し線表記は生産中止					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
9.5-22	6	W/T	242	996	W-8
9.5-24	6	W/T	242	1047	W-8

FSLF					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
7-16	4	W/T	170	740	5-JA
7-16	4	W/T	180	740	6.00F
8-16	4	W/T	193	790	5-JA
9.5-16	4	W/T	248	845	W-8
12.4-16	4	W/T	325	964	W-11
11.2-24	4	W/T	274	1088	W10
11.2-24	6	W/T	274	1088	W10
5-26	4	W/T	122	900	4-JA



FSLW ※打ち消し線表記は生産中止					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
<del>7.2-20</del>	4	W/T	179	845	W-6
11.2-24	4	W/T	280	1088	W-10
11.2-24	6	W/T	285	1088	W-10



FSL					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
11.2-28	4	W/T	287	1206	W-10
11.2-28	6	W/T	287	1206	W-10
12.4-28	4	W/T	320	1262	W-11
12.4-28	6	W/T	320	1262	W-11
14.9-28	6	W/T	387	1370	W-13
16.9-30	6	W/T	436	1485	W-15L
12.4-32	6	W/T	320	1364	W-11
12.4-36	6	W/T	320	1465	W-11
13.6-38	6	W/T	345	1574	W-12



FL00 ※打ち消し線表記は生産中止					
タイヤサイズ	PR	TYPE	断面幅(mm)	外径(mm)	適用リム
7-16	6	W/T	173	740	5-JA
8-16	4	W/T	193	790	5-JA
9.5-16	6	W/T	243	845	W-8
9.5-18	4	W/T	243	895	W-8
9.5-18	6	W/T	243	895	W-8
<del>8.3-20</del>	6	W/T	211	890	W-7
9.5-20	6	W/T	243	945	W-8
11.2-20	6	W/T	284	1003	W-10
8.3-22	6	W/T	210	945	W-7
9.5-22	4	W/T	243	995	W-8
9.5-22	6	W/T	243	995	W-8
<del>8.3-24</del>	6	W/T	205	993	W-7
9.5-24	6	W/T	243	1050	W-8
11.2-24	6	W/T	275	1088	W-10
12.4-24	4	W/T	320	1155	W-11
12.4-24	6	W/T	320	1155	W-11
13.6-24	4	W/T	350	1210	W-12
13.6-24	6	W/T	345	1210	W-12
14.9-24	6	W/T	383	1247	W-13
13.6-26	4	W/T	355	1260	W-12
12.4-28	6	W/T	320	1260	W-11
13.6-28	4	W/T	345	1310	W-12
13.6-28	6	W/T	345	1310	W-12
14.9-28	6	W/T	380	1365	W-13
16.9-28	6	W/T	442	1400	W-15L
16.9-30	6	W/T	442	1485	W-15L
18.4-30	6	W/T	487	1547	W-16L
12.4-32	6	W/T	320	1360	W-11
16.9-34	6	W/T	440	1587	W-15L
18.4-34	6	W/T	478	1635	W-16L
13.9-36	6	W/T	343	1478	W-12
15.5-38	6	W/T	394	1582	W-14L
16.9-38	8	W/T	442	1671	W-15L

TURF

GOLF CAR

A.T.V.

AGRICULTURE

INDUSTRIAL

OFF THE ROAD

TRAILER

LIGHT TRUCK

IMPLEMENT

HAND CART

GO KART

etc.