

LOADERS & DOZERS



XL GRIP

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
12.00-20	20	TT				
16.00-25	28	TL				
16.00-25	32	TL	465	1485	11.25/2.0	12500
17.5-25	12	TL	435	1345	14.00/1.5	6150
17.5-25	16	TL	435	1345	14.00/1.5	7300
18.00-25	32	TL				
18.00-25	40	TL				
20.5-25	12	TL	530	1485	17.00/2.0	6700
20.5-25	16	TL	530	1485	17.00/2.0	8250
23.5-25	16	TL	600	1625	19.50/2.5	9500
23.5-25	20	TL	600	1625	19.50/2.5	10900
26.5-25	20	TL	680	1740	22.00/3.0	13200
29.5-25	28	TT	760	1860	25.00/3.5	17500

※積み降ろし作業時(10km/h)



TR390

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
28L-26	16	TL	714	1560	DW 25 B	4500

※40km/h

Roller & Articulated dump truck



ROCK GRIP E4

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
14.00-24	24	TL				
16.00-25	28	TL	470	1525	11.25/2.0	15525
16.00-25	32	TL	470	1525	11.25/2.0	16875

※10km/h

WHEEL LOADER & BACKHOE



TR 459

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
16.9-24	8	TL				
16.9-24	12	TL	440	1310	DW 15 L	3250
18.4-24	12	TL	472	1375	DW 16 L	3875
19.5L-24	12	TL	490	1325	DW 16 L	3450

※40km/h



AT 621

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
12.5/70-16	8	TL	315	855	10 LB	1645 ^{※1}
15.5/60-18	10	TL	400	950	W 13	2400 ^{※1}
15.5/70-18	10	TL	400	1030	W 13	2700 ^{※1}
17.5/65-20	10	TL	450	1090	W 14 L	3195 ^{※1}
16.9-24	12	TL	450	1302	DW 15L	3250 ^{※2}

※1 10km/h ※2 40km/h

Excavator



EXCAVATOR EM936

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
10.00-20	16	TT	275	1050	7.5	3000
11.00-20	16	TT	295	1090	8.0	3250

※50km/h

Reach Stacker



CONTAINER KING (IND-4)

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
18.00-25	40	TL	528	1675	13.00/2.5	22950

※10km/h

Road Roller



PAC MASTER

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
9.5/65-15	6	TT	235	675	7.0	1320
10.5/80-16	6	TL	275	810	8.0	1850
14.0/70-20	12	TT	380	975	11 TG	4000

※10km/h



TR387

タイヤサイズ	PR	TYPE	総幅 (mm)	外径 (mm)	適用リム	最大荷重 (kg)※
23.1-26	16	TL	587	1560	DW 20 B	4375
16.9-28	8	TL	440	1400	DW 15 L	2180