



















■鋼製壁下地角スタッド一覧

単位：mm

		40×20 40×25	40×40	40×45	40×50	45×65	45×75	45×90	45×100
①角スタッド	[40・20]		[40・40]	[40・45]	[40・50]	[45・65]	[45・75]	[45・90]	[45・100]
	[40・25]								
		t-0.45	t-0.4	t-0.4	t-0.45	t-0.45	t-0.45	t-0.45	t-0.5
②ランナ	[20ランナ]		[40ランナ]	[45ランナ]	[50ランナ]	[65ランナ]	[75ランナ]	[90ランナ]	[100ランナ]
	[25ランナ]								
		t-0.5	t-0.5	t-0.5	t-0.55	t-0.55	t-0.55	t-0.55	t-0.55

■適用高さ一覧表

			40×40	40×45	40×50	45×65	45×75	45×90	45×100
適用高さ	スタッド@303	9.5	3100 2600	3400 2800	3800 3100	4800 4000	5300 4400	6000 5100	6500 5500
		12.5	2900 2400	3200 2600	3500 2900	4500 3700	5000 4100	5700 4800	6200 3200
		9.5 12.5	2500 2000	2700 2100	3000 2400	3800 3100	4300 3500	4900 4000	5300 4300
		12.5 12.5	2400 1900	2600 2000	2900 2300	3700 3000	4100 3400	4800 3900	5200 4000
	@455	9.5 12.5	2200 1800	2400 1900	2700 2100	3400 2700	3800 3100	4400 3500	4800 3900
		12.5 12.5	2100 1700	2300 1800	2600 2000	3300 2600	3700 3000	4200 3400	4600 3700

※1 黒字：片面張り 赤字：両面張り 水平震度1.0Gにて最大たわみL/200以内に於て算出 ※石膏ボードはGB-Rでの検討です